



Europäisches Patentamt
European Patent Office
Office européen des brevets



EP 1 048 895 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
02.11.2000 Bulletin 2000/44

(51) Int Cl.7: F21V 7/00, B60Q 1/04

(21) Application number: 99108131.6

(22) Date of filing: 24.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Howard, Mark Shane
52070 Aachen (DE)


(74) Representative:
Drömer, Hans-Carsten, Dipl.-Ing. et al
Ford-Werke Aktiengesellschaft,
Patentabteilung NH/DRP
50725 Köln (DE)

(71) Applicant: Ford Global Technologies, Inc.,
A subsidiary of Ford Motor Company
Dearborn, Michigan 48126 (US)

(54) Pedestrian protection headlamp

(57) The headlamp includes a headlamp cover (10) with a front surface (10') forming the lens, which cover at its periphery forms a shoulder (14,14',14"). The headlamp further includes a headlamp body (12) arranged rearwardly to the cover's shoulder (14,14',14"). The headlamp is characterized in that, from the shoulder

(14,14',14") of the cover integrated sidewalls (11) extend rearwardly towards the joint (13) where at the end portions of the sidewalls the headlamps body (12) is attached. These integrated sidewalls (11) have mechanically weakened deformable portions (15,15') arranged between the shoulder (14,14',14") and the joint (13).



EP 1 048 895 A1

Description

[0001] The invention concerns the design of a headlamp with optimized properties with respect to pedestrian protection.

[0002] The headlamp consists typically of a headlamp cover with a front surface forming the lens. This cover at its periphery forms a shoulder which is rearwardly connected to the headlamp body.

[0003] According to DE 37 28 552 C 1, the headlamp body in the range of the joint between body and cover is deformable so that in case of a collision the cover may, after deformation of the respective parts of the headlamp body, be moved backwards into the space behind the cover. The joint line between cover and body is surrounded by a frame. In case of a collision, the frame and the front end portions of the headlamp body which are exposed after the cover has been moved backwards, may give rise to a risk of injuries.

[0004] The object of this invention is to reduce the risk of injuries in case of a collision with a pedestrian.

[0005] The headlamp according to the invention includes a headlamp cover with a front surface forming the lens, which cover at its periphery forms a shoulder. The headlamp further includes a headlamp body arranged rearwardly to the cover's shoulder. The headlamp is characterized in that, from the shoulder of the cover integrated sidewalls extend rearwardly towards the joint where at the end portions of the sidewalls the headlamps body is attached. These integrated sidewalls have mechanically weakened deformable portions arranged between the shoulder and the joint.

[0006] By this design, several advantages with respect to a reduced risk of injuries are achieved. The joint between the cover and the headlamp body is moved further away from the front surface of the cover, therefore, the risk that a relatively sharp edge of the cover may injure the pedestrian is reduced.

[0007] Additionally, the weakened portions of the integrated sidewalls allow an optimization with respect to the deformation so that the front surface of the cover can move backwards, but serves as a shield between the pedestrian and the rearward parts of the cover.

[0008] An additional advantage is that the impact energy is absorbed through the deformation of the headlamp body rather than movement of the whole headlamp body.

[0009] The integrated sidewalls would normally be of the same material as the cover, but with respect to the optimization of the deformation a plastically deformable material may be used as an intermediate between the front surface and the body.

[0010] The optimization of the deformation can be achieved by various means. For example, the wall-thickness may be reduced by slots or a groove following an intermediate contour between the shoulder and the joint. The deformation of the sidewalls thus can be controlled by the optimal location of thinner areas of the

sidewalls thickness. In case of a collision with a pedestrian, the cover flattens and there is an increased level of stress in the cover. Stress concentrations occur in the region of the slots (grooves) and this leads to the formation of plastic hinges. The slots are positioned in an optimal manner so that the material is primarily subjected to two dimensional stress field, hence the sidewalls behave in a ductile manner and therefore deform predictably. As the sidewalls begin to fold the deformable portions of the sidewalls are moved inwardly and the front surface of the cover shields the edges.

[0011] Preferably, the cover in the area of the shoulder has an increased wall thickness which serves to improve a shielding function of the covers front surface. This increased wall thickness further way extend along the sidewalls up to the deformable portions which enhances the shielding function of the cover.

[0012] In a preferred embodiment, the cover in the area of the shoulder has a triangular (V-shaped) cross sectional form. Thereby, the shoulder is further stiffened which prevents the sidewalls and/or edges of the body from breaking through the front surface of the cover. Above that the shoulder by this design is mechanically stiffened which supports the inwardly directed deformation of the sidewalls.

[0013] Further details concerning the invention are described with respect to the schematic drawings.

[0014] Fig.1 shows the headlamp arranged in the front left corner of the vehicle in plan view. The headlamp 1 is arranged between the front 2 of the vehicle (e. g. front grille) and the side 3 of the vehicle (fender).

[0015] Fig. 2 shows a cross section II-II as indicated in Fig. 1. The headlamp consists of a cover 10 and a body 12 which are connected to each other by joint 13. The cover 10 has sidewalls 11 which extend rearwardly from the shoulder 14 towards the joint 13. The sidewalls 11 preferably have a wall-thickness which is smaller than the wall-thickness of the front surface 10' of the cover 10. For controlled deformation grooves or slots 15, 15' are arranged in the sidewalls following a contour which is intermediate between the joint 13 and the shoulder 14 Fig. 4).

[0016] As shown in Fig. 3 in case of an impact, the load 16 is distributed along the front surface of the cover. The deformable portions in the sidewalls form plastically deformable hinges which allow controlled deformation as indicated by arrows 17. The V-shaped cross section 14', 14'' mechanically stiffenes the shoulder so that the cover 10 shields the pedestrian against the headlamps body.

Claims

1. Pedestrian protection headlamp including a headlamp cover (10) with a front surface (10') forming the lens, which cover at its periphery forms a shoulder (14, 14', 14'') and further including a headlamp

body (12) arranged rearwardly to the cover's shoulder, characterized in that, from the shoulder (14, 14', 14'') of the cover integrated sidewalls (11) extend rearwardly towards the joint (14) where at the end portions of the sidewalls (11) the cover is attached to the body and wherein the integrated sidewalls (11) have mechanically weakened, deformable portions (15, 15') arranged between the shoulder (14, 14', 14'') and the joint (13).

5

10

2. Pedestrian protection headlamp according to claim 1, characterized in that, the cover (10) in the area of the shoulder (14) has an increased wall-thickness.

15

3. Pedestrian protection headlamp according to claims 1 or 2., characterized in that the cover (10) in the area of the shoulder has a triangular (14', 14'') cross sectional form.

20

25

30

35

40

45

50

55

BEST AVAILABLE COPY




Fig. 1




Fig. 2

BEST AVAILABLE COPY




Fig. 3




Fig. 4

BEST AVAILABLE COPY



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 10 8131

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
A	US 4 475 148 A (TOMFORDE JOHANN) 2 October 1984 (1984-10-02) * column 2, line 59 - column 3, line 8 * * figure 2 *	1	F21M7/00 B60Q1/04
A	US 4 644 447 A (STUERTZ GUENTER ET AL) 17 February 1987 (1987-02-17) * column 2, line 17 - column 3, line 45 * * figures 1-4 *	1	
A,D	DE 37 28 752 C (DAIMLER BENZ AG) 15 December 1988 (1988-12-15) * claim 1; figure 1 *	1	
A	EP 0 620 137 A (VALEO VISION) 19 October 1994 (1994-10-19) * column 4, line 2 - line 27 * * figures 1,2 *	1	
			TECHNICAL FIELDS SEARCHED
			F21M B60Q
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 August 1999	Examiner De Mas, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 99 10 8131

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-08-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4475148 A	02-10-1984	DE 3108059 A	07-10-1982
		FR 2501334 A	10-09-1982
		IT 1149775 B	10-12-1986
		JP 1519103 C	29-09-1989
		JP 57157402 A	29-09-1982
		JP 63066695 B	21-12-1988
US 4644447 A	17-02-1987	DE 3442902 C	12-06-1986
		FR 2573707 A	30-05-1986
		GB 2167548 A, B	29-05-1986
		IT 1182971 B	05-10-1987
		JP 1935997 C	26-05-1995
		JP 6045327 B	15-06-1994
		JP 61129349 A	17-06-1986
		SE 451984 B	09-11-1987
DE 3728752 C	15-12-1988	SE 8505528 A	25-05-1986
		FR 2619770 A	03-03-1989
		GB 2209204 A, B	04-05-1989
		IT 1224715 B	18-10-1990
		JP 1154401 A	16-06-1989
		JP 7019481 B	06-03-1995
		SE 460352 B	02-10-1989
		SE 8802995 A	01-03-1989
EP 0620137 A	19-10-1994	US 4860173 A	22-08-1989
		FR 2703961 A	21-10-1994

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

BEST AVAILABLE COPY